

## Technical Data Sheet

**Product Description** – Dura Grip Clear W/B is a water-based epoxy coating specifically designed to provide a barefoot-friendly, durable, textured surface for foot traffic on fiberglass, metal, treated aluminum, concrete, wood, tile and natural stone. Dura grip W/B Clear is ideal for use on boat decks, trailers, steps, ramps, and other locations where anti-slip protection is needed. This easy-to-apply coating can be used for light industrial, commercial and residential areas where increased traction is desired.

### SlipDoctors Dura Grip Clear W/B

#### Special Features

- Interior and Exterior Use
- Easy to Apply
- Increases Traction
- 100% Clear Coating
- Barefoot Friendly
- Low Odor & VOC
- Environmentally Friendly
- UV Resistant

#### Suggested Uses

- Commercial and Residential Use
- Boats & Boat Decks
- Laundry Rooms
- Bathrooms
- Steps
- Ramps
- Entries & Walkways
- Patios

### Product Characteristics

<b>Surfaces</b>	Steel, fiberglass, metal, aluminum, concrete, wood, tile & natural stone
<b>Color</b>	Clear
<b>Mode of Application</b>	3/8" Nap roller
<b>Container Size</b>	quart, gallon & 5 gallon pail
<b>Application Temperature</b>	Surface temp is between 50-90°F (10-32°C); must be > 5°F (-15°C) above the dew point
<b>Dry Time</b>	Foot Traffic 24 hours
<b>Recoat Time</b>	2-4 hours
<b>Water Resistant</b>	Yes, cannot be submerged
<b>Stain Resistant</b>	Yes
<b>Product Type</b>	Water-based epoxy ester coating
<b>Coverage</b>	300 sq.ft./gallon
<b>Storage</b>	Room temperature in a well-ventilated area; Do not freeze
<b>Shelf Life</b>	2 years unopened, 1 year opened
<b>Warranty</b>	2 years
<b>Removal</b>	Paint stripper
<b>Disposal</b>	Dispose of container and unused contents in accordance with local, state and federal regulations.

## Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using. Immediately wash off product if it comes in contact with skin.

### Safety Precautions

- Immediately wash off product with soap and water if product comes in contact with skin.
- Use product in a well-ventilated area.
- If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or [www.epa.gov/lead](http://www.epa.gov/lead)

### Recommended Safety Equipment

- Chemical-resistant gloves
- Eye protection
- Mask

### Surface Preparation

Surface Preparation varies by surface. Please see chart below for specific surface preparation instructions.

### Application Instructions

- Step 1:** For exterior applications, check weather conditions to be certain rain or dew is not imminent before product has had the opportunity to dry fully after application.
- Step 2:** **TEST:** Dura Grip Clear W/B should be tested on a small inconspicuous area before full application.
- Step 3:** **MIXING:** Use paint shaker or hand stir to thoroughly mix before using. Stir occasionally during use. Do not mix Dura Grip Clear W/B with any compound containing solvent.
- Step 4:** **APPLICATION:** May be applied in 1-2 coats (2 coats recommended). For best performance, avoid thick coats. Using a 3/8" nap roller, apply Dura Grip Clear W/B in uniform coats applying with light even pressure. Once dry to touch (2-4 hours), second coat should be applied at a right angle to the first coat.
- Step 5:** **CLEAN UP:** While Dura Grip Clear W/B is still wet, equipment may be cleaned with soap and water. Once dried, equipment may be cleaned with a solvent such as xylene or toluene.

### Maintenance

For general cleaning and maintenance, use a light pressure rinsing. For best results to remove oily deposits or other foreign matter, apply pH-neutral cleaner at recommended dilution rate and scrub lightly with a soft bristle deck brush.

### Surface Preparation

Surface Type	Surface Preparation
All Surfaces	All substrates must be cleaned, dry and free of dust, dirt, oil, grease, soil, soap residue, wax, flaking paint and other soluble contaminants.
Uncoated Concrete	New concrete should be allowed to cure for 30 days before application of any coating. If there is any doubt about the dryness of the concrete, conduct a test by simply placing a weighted rubber mat, plastic sheet or other nonporous material on the surface for 24 hours. Check the underside of the mat and concrete for signs of moisture. The concrete will be darker if damp. If moisture is found, allow additional dry time (10-14 days) and repeat test. If moisture persists, the concrete surface cannot be coated.

<b>Previously Coated Surfaces</b>	Scrape and sand peeled or chipped paint to a sound surface. Once surface is free of coating lightly scuff surface to promote adhesion. Clean again ensuring the surface is free of all dust and residue. Allow to completely dry before application.
<b>Wood</b>	Patch all holes and imperfections with a wood filler or putty and sand smooth. Sand any exposed wood to a fresh surface. Mold and mildew must be cleaned with a chlorinated cleaner or bleach solution. Remove all surface contamination by washing with a pH-neutral cleaner, rinse thoroughly and allow to dry.
<b>Fiberglass</b>	Lightly sand fiberglass with 220 grit sandpaper. Clean surface with pH neutral cleaner or acetone. Rinse thoroughly and allow to dry.
<b>Tiles &amp; Natural Stone</b>	Glossy surfaces should be de-glossed by lightly sanding or using a chemical de-glosser, such as SlipDoctors Stone Grip, before using Dura Grip W/B. Clean surface using pH-neutral cleaner, rinse and allow to thoroughly dry before application.
<b>Aluminum/Metal</b>	Loose rust, mill scale and deteriorated previous coatings must be removed by hand tool or power tool cleaning. A power Brushoff Abrasive Blast may be used as an alternative to scraping and wire brushing. Scuff, sand and dull all slick hard, glossy surfaces to promote adhesion. Heavily rusted areas may require a Commercial Grade Blast to assure maximum coating performance. <b>ALUMINUM SURFACES MUST BE SCUFFED AND/OR ETCHED WITH SLIPDOCTORS STONE GRIP BEFORE APPLICATION OF DURA GRIP CLEAR W/B.</b>

## Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions List and First Aid Instructions  
Dura Grip Clear W/B Safety Data Sheet can be found at [www.slipdoctors.com](http://www.slipdoctors.com)

**Technical Support:** Please contact SlipDoctors at 1-888-436-5404 or support@slipdoctors.com.  
**Office Hours:** Monday - Friday from 8:00 am - 5:00 pm CST.

## Warranty & Disclaimer

**WARRANTY:** All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for 2 years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the seller nor the manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by seller and manufacturer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit [www.slipdoctors.com](http://www.slipdoctors.com) to find further warranty information.

Revised 6/28/17